# Large LED Screen Temperature/ Humidity Monitor

## Features

- Complete environmental monitor alarm
- Wall Mounted LED type, easy read
- Alarm set for Hi and Low limit Temperature and Humidity
- Data Logging Capacity 30,000 recc
- LED displays real time data
- USB interface

## Specifications

- Temperature range: -4 to 140oF ( -20o to 60oC)
- Temp. accuracy: +/-1.8oF / +/-1.0oC (23o to 104oF 5.0o to 40.0oC ) other 3.6oF/2.0oC
- Temp. resolution: 0.1oF/0.1oC
- Temp. update rate: times/second
- Temp. sensor type: Diode
- Relative Humidity range: 5% to 95%
- Relative Humidity accuracy: +/-2.5%RH (at 25oC. 20% to 80%)
- other : +/-5.0%RH (at 25oC,90%RH)
- Relative Humidity resolution: 1.0 RH
- Relative Humidity response time: below 4 seconds
- LED display: 8.4x4.73 inch (214mm x 120mm)
- Power supply: AC to DC Adapter (9V/1A)
- Battery backup: DC 9V battery enables continued recording without display reading during power disruption for an hour only.
- Size: 260 x 178 x 47mm
- Weight: 1000g

Office: Jl. Radin Inten II No. 62 Duren Sawit, Jakarta 13440 - Indonesia
Workshop: Jl. Pahlawan Revolusi No. 22B, Jakarta 13430 - Indonesia
Phone: 021-8690 6777 (Hunting)

Mobile: +62 816 1740 8925
Fax: 021-8690 6771