




AT5030C



High resolution image



Friendly operation keyboard

◆ General Specification :

Tunnel Size: 500mm×300mm
Conveyor Speed: 0.22m/s
Conveyor height : 663mm
Conveyor Max Load:150kg
X ray Dose per inspection <0.1.25μSv
Wire Resolution: 38AWG guarantee, 40 AWG typical
Spatial resolution Level: dia1.0mm,Vertical: dia1.0mm
Penetration: 30mm steel guarantee ,32mm steel typical
Film Safety :Guarantee ASA/ISO1600 Film
X-ray Leakage: <0.87 μSv/h (at a distance of 5cm From external housing)

◆ Image System :

Technical Principle: Dual-energy X-ray Imaging; L Shaped Array,
X-ray Sensor: L-Shaped Photodiode Array (**multi-energetic**)
Monitor: High Resolution Color, LCD Accord, 17inch
Image Display: High resolution of 1024 * 1280 pixel; Image Grey Level: 65536
Image Enhancement: 1-64times enlargement continuity, Color/BW, negative, high/low penetration, organic /inorganic Stripping, general enhancement, and pseudo color, etc.
Image Recall: All preceding images recallable, retrieval.
Explosives & Narcotics Detection: Assist suspicious Explosives & narcotics alarm and highlight according to atomic number signature
High Density Region Alarm: Impenetrable region alarm and highlight, for possible concealing of threats and contrabands
Threat Image Projection: Inserting fictional, but realistic images of threat items into baggage during screening operation, for maintenance of vigilance, as well as training and assessment of image identification capability
Image Archive: Up to 100,000 images stored automatically, enable transferring to USB disk, and converting to JPG, BMP and other general formats
Miscellaneous Functions : Time/date display, counters, user management, system-on/X-ray-on timers, power on self test, built-in diagnostic facilities, dual-direction scanning, system log, system standby,etc.
Network Applications: Multiple remote applications available based on Ethernet LAN and windows platform, such as image centralized storage and identify, recheck workstation, and network TIP, etc (Optional) .
Images process: 24bit real time processing ,4colors analysis, Images displayed marked date and ID NO ,Count the number of bags ,Memory gray level:65536

◆ Operating Environment:

Operation temperature/Humidity: 5°C-40°C/10%-95%(non-condensing)
Storage Temperature/Humidity: -20°C to 60°C / 5%-95%(non-condensing)
Operation Power: 220VAC(±10%)50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)
Power Consumption: 1.0KW (max), 0.7KW(working)
Noise: <58db
Dimension Size
Dimensions (L×W×H) :1660mm x746mm x1165 mm
Device Weight: 330Kg
G.Weight: 470Kg
Packing Volume: 2.35CBM

◆ Computer Character:


CASE: GT6058
Power: 300W/ATX
Main board: H61 SYM76993VGGA
CPU: G1610 2.6G
Storage: 2GB 1600MHz DDR3 Innodisk
Hard Disk: SEAGATE 500G 3.5"

◆ X-ray Generator:

Anode Voltage: 140kv
Anode power: 0.35mA
Generate angle: 80 degree upward
Brand: SECUSCAN (own made)
Generate direct: from bottom to top
Cooling / Duty Cycle: Oil Cooling /100%

◆ Other Characters:

Detect PCB board: UK brand Sensortech
Extension Rollers: customize size length
Support card reader operator access
CD DVR/RW unit: Optional
Computer system: XP system
UPS: 15mins, 30mins, 60mins etc, optional



Certificates: ☆ISO19001 ☆ISO14001 ☆OHSMS18001 ☆CE ☆Health Inspection Report ☆Computer Software Copyright Registration Certificate ☆Software Product Registration Certificate ☆ Certificate from Ministry of Public Security ☆Safety and Police Electronic Products Quality Inspection Center ☆Patent No. : 201020700245.2 ☆Patent No. : 201020700245.8 ☆Patent No. : 201020700256.0